

TIPO -MODEL	AR60M		AR110		AR160		AR200	
	Dimensioni Dimensions	Ø Int. Min Inside Diameter	Dimensioni Dimensions	Ø Int. Min Inside Diameter	Dimensioni Dimensions	Ø Int. Min Inside Diameter	Dimensioni Dimensions	Ø Int. Min Inside Diameter
1 ●	70 x 10 25 x 5 2" 3/4 x 3/8 1" x 0.2"	1.500 500 59" 20"	110 x 25 40 X 10 4"-3/8 x 1" 1"-9/16 x 3/8"	1.400 380 55" 15"	150 x 40 50 X 10 6" x 9/16" 2" x 3/8"	1.500 600 59" 24"	180 x 45 2.200 7" x 1-3/4" 86"	
2 ●	100 x 20 4" x 3/4"	1.400 55"	180 x 30 7" x 1"-1/8"	1.000 40"	240 x 50 9" 3/8 x 2"	1.800 71"	280 x 60 2.300 11" x 2" 3/8" 90"	
3 ●	38 1"-1/2"	500 20"	60 2"-3/8"	1.200 47"	95 3"-3/4"	2.500 98"	115 3.400 4" 5/8" 134"	
4 ●	35 1"-3/8"	500 20"	75 3"	750 30"	110 4"-3/8"	1.650 65"	135 2.000 5" 5/16" 79"	
5 ■	60 x 3 2" 3/8 x 0.120"	1.000 40"	140 x 3 5"-1/2 x 0.120"	2.800 110"	168,3 x 7 6"-5/8 x 1/4"	3.000 118"	273 x 9 8.000 10" 3/4 x 0.354" 315"	
6 ●	70 x 20 x 3 2" 3/4 x 3/4 x 0.120"	1.000 40"	100 x 50 x 5 4" x 2" x 0.2"	1.200 47"	180 x 70 x 8 7 x 2"-5/8 x 5/16"	3.000 118"	200 x 80 x 8 6.600 8" x 3" 1/8 x 2/3 260"	
7 ▲	60 x 3 2" 3/8 x 0.120"	1.500 59"	90 x 5 3"-1/2 x 0.2"	2.000 79"	125 x 10 5" x 3/8"	1.500 59"	165 x 10 6.000 6" 1/2 x 3/8" 236"	
8 ●	60 x 4 30 x 4 2"-3/8 x 0.157" 1"-1/8 x 0.157"	1.800 500 70" 20"	100 x 10 4" x 3/8"	2.000 79"	150 x 15 6" x 2/3"	4.500 149"	200 x 18 6.400 8" x 11/16" 252"	
9 ★	60 x 60 x 6 30 x 4 2"-3/8 x 0.240" 1"-1/8 x 0.157"	1.000 500 40" 20"	90 x 10 40 x 5 3"-1/2 x 3/8" 1"-9/16 x 0.2"	2.600 520 102" 50"	125 x 10 5" x 3/8"	5.000 197"	180 x 18 6.400 7" x 11/16" 252"	
10 ●	60 2"-3/8"	1.000 40"	100 4"	1.600 63"	140 x 12 5"-1/2 x 1/2"	3.000 118"	200 x 20 7.400 8" x 3/4" 291"	
11 ●	60 2"-3/8"	1.000 40"	100 4"	1.600 63"	120 x 13 4"-3/4 x 0.511"	5.000 197"	200 x 20 7.400 8" x 3/4" 291"	
12 ●	60 2"-3/8"	1.000 40"	100 4"	1.600 63"	120 x 13 4"-3/4 x 0.511"	5.000 197"	200 x 20 7.400 8" x 3/4" 291"	
13 ●	80x45 3"-1/8" x 1"-3/4"	1.000 40"	120 4" x 3/4"	1.200 79"	200 8"	4.500 177"	280 6.300 11" 248"	
14 ●	80x45 3"-1/8" x 1"-3/4"	1.000 40"	120 4" x 3/4"	1.200 79"	200 8"	4.500 177"	280 6.300 11" 248"	
15 ●	IPE		140 5"-1/2"	3.000 118"	240 9"	4.500 177"	280 6.300 11" 248"	
16 ★	HE		A = 140 B = 120 A = 5"-1/2 B = 4"-3/4"	A = 3.000 B = 5.000 63" 63"	A = 180 B = 160 M = 100 A = 7" B = 6" M = 4"	6.000 6.000 6.000 236" 236" 236"	A = 240 B = 200 M = 140 A = 9" B = 8" M = 5"	12.000 10.000 10.000 473" 394" 394"
17 ★	UNP		100 4"	2.400 94"	180 7"	12.000 472"	240 10.000 9" 394"	
18 ★	INP		100 4"	3.000 118"	180 7"	9.000 354"	240 10.000 9" 394"	
19 ★	HE		B = 120 B - 4"-3/4"	5.800 228"	A = 180 B = 160 A = 8" B = 6"	3.400 9.000 315" 354"	A = 240 B = 200 A = 9" B = 8"	10.000 9.500 394" 374"
Wcm <sup>3</sup> Max	25 25		157 157		420 420		1.860 1.860	
Velocità di rotolamento Inches / min speed	5 237		5 237		5 237		5 237	
Potenza Kw HP Power	3 4		7,5 10		18,5 25		30 40	
Ø alberi Shafts diameter	mm. "	60 2.375"	110 4.33"		160 6.30"		210 8.27"	
Ø rulli Rolls diameter	mm. "	215 8.46"	350 13.78"		485 19.10"		650 25.60"	
Peso Weight	Kg. Lbs.	920 2.026	2.950 6.498"		6.800 14.980"		24.000 52.800"	

LEGENDA

- Curvatura con rulli standard - Bending with standard rolls - Cintrage avec rouleaux standard - Curvado con rulas estandard
- Un set rulli ogni diametro tubi - One set of rolls for each pipe diameter - Un set de rouleaux chaque diametre de tube - Un set de rulas para cada diámetro de tubo
- ★ Curvatura con attrezzatura speciale - Rolling with special tooling - Cintrage avec outils spéciaux - Curvado con herramienta especial